BDC 1,5 ... 30 MHz
Richtkoppler

BONN Elektronik
YOUR ULTIMATE RF POWER SOURCE

STANDARDMODELLE


Modell	Frequenzbereich X)	Kopplung X) dB	Leistung Pmin W	Dämpfung max dB	Richtschärfe min dB	VSWR max Hauptarm	Hauptarm Stecker 1), 2)	Koppelarm Stecker 3)
BDC 0103-40/500	**1,5 ... 30 MHz**	**40 ±1,25**	**500**	**0,1**	**25**	**1.3:1**	**N-f**	**SMA-f**

S: Einzel-Richtkoppler

OPTIONEN

1) Männlicher Stecker am HF-Eingang
2) Andere Steckerart am Hauptarm
3) N-f Stecker an den Koppelports
X) Spezielle Frequenzbereiche und Koppeldämpfungen auf Anfrage

Dieses Dokument ist Eigentum der Firma Bonn Elektronik GmbH.
Vervielfältigung und Veröffentlichung ohne ausdrückliche Genehmigung ist untersagt. Änderungen im Sinne des technischen Fortschritts können ohne Vorankündigungen vorgenommen werden. Wenn nichts anders angegeben alle Maße Millimeter.



Product Information		**Entwurf** 25.01.18 Bonn
10014924		
Directional Coupler		**Zeichnung** 25.01.18 Bhu
BDC 0103-40/500		**Prüfung**
BONN Elektronik info@bonn-elektronik.com • www.bonn-elektronik.com	**1-1**	**Freigabe** 05.02.18 Bonn

Schutzvermerk nach DIN ISO 16016 beachten Observe copyright indication DIN ISO 16016
ISO - Projection

This document is the property of Bonn Elektronik GmbH.
Reproduction and release without express permission is strictly prohibited.
We reserve the right to introduce modifications without prior notification, where they serve technical progress. Unless otherwise indicated all dimensions millimeters.