

STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 1040-30/20D	1 ... 4 GHz				200	3 HU, 430 mm	19
	1 ... 2 GHz	30 / 35	44.8 / 47 ±2	20 / 20			
	2 ... 4 GHz	20 / 35	43 / 45 ±2	20 / 20			
BLMA 1040-30	1 ... 4 GHz	30 / 35	44.8 / 47 ±2	15 / 20	300	2 HU, 430 mm	12
BLMA 1040-60/35D	1 ... 4 GHz				400	3 HU, 630 mm	22
	1 ... 2 GHz	60 / 70	47.8 / 50 ±2	20 / 20			
	2 ... 4 GHz	35 / 40	45.4 / 48 ±2	20 / 20			
BLMA 1040-60	1 ... 4 GHz	60 / 80	47.8 / 50 ±2	18 / 20	600	3 HU, 430 mm	17
BLMA 1040-60D	1 ... 4 GHz				600	3 HU, 630 mm	26
	1 ... 2 GHz	60 / 70	47.8 / 50 ±2	20 / 20			
	2 ... 4 GHz	60 / 75	47.8 / 50 ±2	20 / 20			
BLMA 1040-80	1 ... 4 GHz	80 / 100	49 / 51 ±2	20 / 20	490	3 HU, 430 mm	18
BLMA 1040-120	1 ... 4 GHz	120 / 150	50.8 / 53 ±2	20 / 20	1200	3 HU, 630 mm	26
BLMA 1040-200	1 ... 4 GHz	200 / 250	53 / 55 ±2	20 / 20	1600	4 HU, 630 mm	40
BLMA 1040-250	1 ... 4 GHz	250 / 280	54 / 56 ±2	20 / 20	1600	4 HU, 630 mm	39
BLMA 1040-300/200	1 ... 4 GHz				3900	8 HU, 630 mm	87
	1 ... 2 GHz	300 / 320	54.8 / 57 ±2	20 / 20			
	2 ... 4 GHz	200 / 240	53 / 55 ±2	20 / 20			
BLMA 1040-400	1 ... 4 GHz	400 / 500	56 / 59 ±3	20 / 20	3700	5 HU, 630 mm	62
BLMA 1040-500	1 ... 4 GHz	500 / 600	57 / 59 ±2	18 / 20	6000	8 HU, 630 mm	97
BLMA 1040-750	1 ... 4 GHz	750 / 800	58.8 / 62 ±3	20 / 20	8000	12 HU, 800 mm	140
BLMA 1040-1000	1 ... 4 GHz	1000 / 1150	60 / 62 ±2	20 / 20	8000	18 HU, 800 mm	210

For individual data sheets, please click on the above model name

1 HU = 44.45 mm