

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 0760-2	0.7 ... 6 GHz	2 / 2.2	33 / 35 ±3	20 / 20	50	2 HU, 430 mm	10
BLMA 0760-3	0.7 ... 6 GHz	3 / 3.3	34.8 / 37 ±3	20 / 20	90	2 HU, 430 mm	10
BLMA 0760-6	0.7 ... 6 GHz	6 / 10	37.8 / 40 ±3	15 / 20	160	2 HU, 430 mm	10
BLMA 0760-15	0.7 ... 6 GHz	15 / 20	41.8 / 45 ±3	15 / 20	250	2 HU, 430 mm	12
BLMA 0760-25	0.7 ... 6 GHz	25 / 30	44 / 47 ±3	20 / 20	500	2 HU, 430 mm	13
BLMA 0760-50	0.7 ... 6 GHz	50 / 55	47 / 50 ±3	15 / 20	600	2 HU, 430 mm	14
BLMA 0760-75	0.7 ... 6 GHz	75 / 100	48.8 / 52 ±3	18 / 20	1100	3 HU, 430 mm	22
BLMA 0760-100	0.7 ... 6 GHz	100 / 115	50 / 53 ±3	18 / 20	1400	3 HU, 430 mm	22
BLMA 0760-125	0.7 ... 6 GHz	125 / 140	51 / 54 ±3	20 / 20	1450	4 HU, 630 mm	38
BLMA 0760-150	0.7 ... 6 GHz	150 / 170	51.8 / 55 ±3	15 / 20	1600	4 HU, 630 mm	38
BLMA 0760-180	0.7 ... 6 GHz	180 / 200	52.6 / 56 ±3	20 / 20	3200	5 HU, 630 mm	58
BLMA 0760-200	0.7 ... 6 GHz	200 / 220	53 / 56 ±3	20 / 20	3100	5 HU, 630 mm	58
BLMA 0760-250	0.7 ... 6 GHz	250 / 280	54 / 57 ±3	20 / 20	4500	7 HU, 630 mm	85
BLMA 0760-300	0.7 ... 6 GHz	300 / 330	54.8 / 58 ±3	20 / 20	5000	7 HU, 630 mm	85
BLMA 0760-400	0.7 ... 6 GHz	400 / 450	56 / 59 ±3	20 / 20	5000	10 HU, 630 mm	121
BLMA 0760-500	0.7 ... 6 GHz	500 / 550	57 / 60 ±3	20 / 20	7000	10 HU, 630 mm	160
BLMA 0760-750	0.7 ... 6 GHz	750 / 800	58.8 / 62 ±3	15 / 20	10000	18 HU, 800 mm	190
BLMA 0760-1000	0.7 ... 6 GHz	1000 / 1100	60 / 63 ±3	15 / 20	15000	24 HU, 800 mm	260

For individual data sheets, please click on the above model name

1 HU = 44.45 mm