

### STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 9396-10	930 ... 960 MHz	10 / 13	40 / 42 ±2	25 / 25	75	2 HU, 430 mm	11
BLWA 9396-25	930 ... 960 MHz	25 / 30	44 / 46 ±2	25 / 25	150	2 HU, 430 mm	12
BLWA 9396-50	930 ... 960 MHz	50 / 60	47 / 49 ±2	50 / 50	300	3 HU, 430 mm	15
BLWA 9396-100	930 ... 960 MHz	100 / 115	50 / 52 ±2	50 / 50	500	3 HU, 430 mm	18
BLWA 9396-200	930 ... 960 MHz	200 / 220	53 / 55 ±2	50 / 50	1200	4 HU, 630 mm	35

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

### STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant) $P_N$ -0.5 dB min. at VSWR 2:1
Spurious (at $P_N$ ):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A linear or A-B linear

### GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	standard on rear panel $P_N$ up to 1 kW N-f $P_N$ >1 kW 7-16-f $P_N$ >2 kW 13-30-f or 1 5/8" EIA
Mains Supply:	Line Power: <1000 VA 100 ... 240 V AC ±10% 1000 ... 3000 VA 200 ... 240 V AC ±10% >3000 VA 3x 400 V AC ±10%
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

## OPTIONS

---

- |                                      |   |
|--------------------------------------|---|
| A) RF-Sample Ports                   | I) 3x 208 V AC / 60 Hz                  |
| B) External Dual Directional Coupler | L) LAN Remote Control                   |
| C) IEEE-488.2 GPIB Remote Control    | S) Internal RF Switching Unit           |
| D) Front Panel RF Connectors         | R) RS-232C Remote Control               |
| E) RF Power Indication (digital)     | U) USB Remote Control                   |
| F) Gain Adjustment                   | W) Liquid Cooling                       |
| H) DC Supply                         | X) External Control of other Amplifiers |