

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 2325-10	2.3 ... 2.5 GHz	10 / 13	40 / 42 ±2	50 / 50	80	2 HU, 430 mm	12
BLMA 2325-25	2.3 ... 2.5 GHz	25 / 30	44 / 46 ±2	50 / 50	180	2 HU, 430 mm	18
BLMA 2325-50	2.3 ... 2.5 GHz	50 / 60	47 / 49 ±2	50 / 50	400	3 HU, 430 mm	25
BLMA 2325-100	2.3 ... 2.5 GHz	100 / 110	50 / 52 ±2	50 / 50	800	3 HU, 630 mm	28
BLMA 2325-150	2.3 ... 2.5 GHz	150 / 165	51.8 / 54 ±2	50 / 50	1500	4 HU, 630 mm	45

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant) P_N -0.5 dB min. at VSWR 2:1
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear or AB-linear

GENERAL

RF Input:	<12 GHz 12 bis 18 GHz >18 GHz	N-f, standard on rear panel SMA-f, standard on front panel 2.92 mm-f, standard on front panel
RF Output:	<12 GHz 12 to 18 GHz >18 GHz	N-f, standard on rear panel SMA-f, standard on front panel 2.92 mm-f, standard on front panel
Mains Supply:	Line Power: Line Power <800 VA 800 ... 3000 VA >3000 VA	100 ... 240 V AC ±10% 200 ... 240 V AC ±10% 3x 400 V AC ±10%
Elapsed Time Meter:	via status display	
Ambient Temperature:	0 ... +45 °C	
Storage Temperature:	-20 ... +85 °C	
Relative Humidity:	up to 95% (non-condensing)	
Operating Altitude:	up to 2000 m above sea level	
Vibration and Shock:	MIL-STD-810 G	
Cooling:	forced air with integral blower air intake from front, air exhaust at rear	

Narrow Band Amplifiers 2.3 ... 2.5 GHz

Solid State Amplifiers

OPTIONS

- | | |
|--------------------------------------|---|
| A) RF-Sample Ports *) | L) LAN Remote Control |
| B) External Dual Directional Coupler | N) Harmonics Filtering *) |
| C) IEEE-488.2 GPIB Remote Control | R) RS-232C Remote Control |
| D) Front Panel RF Connectors | S) Internal RF Switching Unit *) |
| E) RF Power Indication (digital) *) | U) USB Remote Control |
| F) Gain Adjustment *) | W) Liquid Cooling |
| G) Output Isolator *) | X) External Control of other Amplifiers |
| H) DC Supply | |
| I) 3x 208 V AC / 60 Hz | |

*) These options may reduce output power and/or gain