

## STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
TWAL 1826-40	18 ... 26.5 GHz	40 / 60	46 / 52 ±6	20 / 20	900	3+3 HU, 630 mm	40
TWAL 1826-40E	18 ... 26.5 GHz	40 / 60	46 / 52 ±6	20 / 20	750	4 HU, 630 mm	35
TWAL 1826-80	18 ... 26.5 GHz	80 / 100	49 / 55 ±6	20 / 20	1800	12 HU, 800 mm	115
TWAL 1826-120	18 ... 26.5 GHz	120 / 150	50.8 / 57 ±6	20 / 20	750	6 HU, 630 mm	38
TWAL 1826-200	18 ... 26.5 GHz	200 / 220	53 / 59 ±6	20 / 20	1500	15 HU, 630 mm	115

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant) $P_N$ -0.5 dB min. at VSWR 2:1
Spurious (at $P_N$ ):	-50 dBc typ. (excluding harmonics)
Noise Figure	20 dB max.
Class of Operation:	A-linear

## GENERAL

RF Input:	1 ... 18 GHz	N-f; standard on rear panel
	18 ... 40 GHz	2.92 mm-f; standard on rear panel
RF Output (up to 1 kW):	1 ... 18 GHz	N-f
	6 ... 18 GHz	WRD 650
	8 ... 18 GHz	WRD 750
	18 ... 26,5 GHz	WR 42
	26,5 ... 40 GHz	WR 28
RF Output (1 kW or more):	1 ... 8 GHz	7-16-f
	8 ... 18 GHz	WRD 750
Mains Supply:	200 ... 240 V AC	47 ... 63 Hz
Elapsed Time Meter:	via status display	
Ambient Temperature:	0 ... 45 °C	
Storage Temperature:	-20 ... +85 °C	
Relative Humidity:	up to 95% (non-condensing)	
Operating Altitude:	up to 2000 m above sea level	
Vibration and Shock:	normal laboratory environment	
Cooling:	forced air with integral blower air intake and exhaust at rear	

## OPTIONS

---

- |                                      |                                         |
|--------------------------------------|-----------------------------------------|
| A) RF Monitor Outputs *)             | N) Harmonic Filter *)                   |
| B) External Dual Directional Coupler | R) RS-232C Remote Control               |
| C) IEEE-488.2 GPIB Remote Control    | S) Internal RF Switching Unit *)        |
| D) Front Panel RF Connectors         | U) USB Remote Control                   |
| E) RF Power Indication (digital) *)  | W) Liquid Cooling                       |
| F) Gain Adjustment *)                | X) External Control of other Amplifiers |
| G) Output Isolator *)                |                                         |
| L) Remote Control                    |                                         |

\*) These options may reduce output power and/or gain