

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 2050-100	200 ... 500 MHz	100 / 120	50 / 52 ±2	20 / 15	400	3 HU, 430 mm	19
BLWA 2050-150	200 ... 500 MHz	150 / 180	51.8 / 54 ±2	20 / 15	800	3 HU, 430 mm	24
BLWA 2050-300	200 ... 500 MHz	300 / 330	54.8 / 57 ±2	20 / 20	1500	3 HU, 630 mm	35
BLWA 2050-500	200 ... 500 MHz	500 / 600	57 / 59 ±2	20 / 20	2500	5 HU, 630 mm	43
BLWA 2050-750	200 ... 500 MHz	750 / 850	58.8 / 61 ±2	20 / 20	4000	6 HU, 630 mm	80
BLWA 2050-1000	200 ... 500 MHz	1000 / 1150	60 / 62 ±2	20 / 20	6000	8 HU, 630 mm	120
BLWA 2050-1500	200 ... 500 MHz	1500 / 1700	61.8 / 64 ±2	20 / 20	8000	16 HU, 630 mm	180
BLWA 2050-2000	200 ... 500 MHz	2000 / 2200	63 / 65 ±2	20 / 20	10000	19 HU, 630 mm	200
BLWA 2050-2500	200 ... 500 MHz	2500 / 2700	64 / 66 ±2	20 / 20	17000	41 HU, 800 mm	300
BLWA 2050-3500	200 ... 500 MHz	3500 / 4000	65.4 / 68 ±2	20 / 20	20000	41 HU, 800 mm	400
BLWA 2050-4500	200 ... 500 MHz	4500 / 5000	65.5 / 68 ±2	20 / 20	35000	2x 32 HU, 800 mm	600
BLWA 2050-6000	200 ... 500 MHz	6000 / 6500	67.8 / 70 ±2	20 / 20	45000	2x 32 HU, 800 mm	600

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	P_N -0.5 dB min. at VSWR 2:1
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A linear or A-B linear

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	standard on rear panel
	P_N up to 1 kW N-f
	P_N >1 kW 7-16-f
	P_N >2 kW 13-30-f or 1 5/8" EIA
Mains Supply:	Line Power:
	<1000 VA 100 ... 240 V AC ±10%
	1000 ... 3000 VA 200 ... 240 V AC ±10%
	>3000 VA 3x 400 V AC ±10%
Elapsed Time Meter:	via status display

BLWA 200 ... 500 MHz Solid State Amplifiers

Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

OPTIONS

A) RF-Sample Ports	I) 3x 208 V AC / 60 Hz
B) External Dual Directional Coupler	L) LAN Remote Control
C) IEEE-488.2 GPIB Remote Control	S) Internal RF Switching Unit
D) Front Panel RF Connectors	R) RS-232C Remote Control
E) RF Power Indication (digital)	U) USB Remote Control
F) Gain Adjustment	W) Liquid Cooling
H) DC Supply	X) External Control of other Amplifiers