

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 4018-5	4 ... 18 GHz	5 / 6	37 / 39 ±2	18 / 20	200	2 HU, 430 mm	12
BLMA 4018-10	4 ... 18 GHz	10 / 12	40 / 44 ±4	18 / 18	300	2 HU, 430 mm	13
BLMA 4018-20/15D	4 ... 18 GHz				380	3 HU, 430 mm	21
	4 ... 6 GHz	20 / 25	43 / 45 ±2	20 / 20			
	6 ... 18 GHz	15 / 18	41.8 / 46 ±4	15 / 20			
BLMA 4018-20D	4 ... 18 GHz				400	3 HU, 430 mm	23
	4 ... 6 GHz	20 / 25	43 / 45 ±2	20 / 20			
	6 ... 18 GHz	20 / 22	43 / 46 ±3	15 / 20			
BLMA 4018-30D	4 ... 18 GHz				700	4 HU, 630 mm	37
	4 ... 6 GHz	30 / 35	44.8 / 47 ±2	20 / 20			
	6 ... 18 GHz	30 / 35	44.8 / 47 ±3	15 / 20			
BLMA 4018-40/35D	4 ... 18 GHz				700	4 HU, 630 mm	37
	4 ... 6 GHz	40 / 45	46 / 48 ±2	20 / 20			
	6 ... 18 GHz	35 / 40	45.4 / 48 ±3	15 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm [1 mW] max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	P_N -0.5 dB min. at VSWR 2:1
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear or AB-linear

GENERAL

RF Input:	<12 GHz	N-f, standard on rear panel
	12 bis 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
RF Output:	<12 GHz	N-f, standard on rear panel
	12 to 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
Mains Supply:	Line Power:	
	Line Power	
	<800 VA	100 ... 240 V AC ±10%
	800 ... 3000 VA	200 ... 240 V AC ±10%

BLMA 4 ... 18 GHz Solid State Amplifiers

	>3000 VA	3x 400 V AC ±10%
Elapsed Time Meter:	via status display	
Ambient Temperature:	0 ... +45 °C	
Storage Temperature:	-20 ... +85 °C	
Relative Humidity:	up to 95% (non-condensing)	
Operating Altitude:	up to 2000 m above sea level	
Vibration and Shock:	MIL-STD-810 F	
Cooling:	forced air with integral blower air intake from front, air exhaust at rear	

OPTIONS

A) RF-Sample Ports *)	L) LAN Remote Control
B) External Dual Directional Coupler	N) Harmonics Filtering *)
C) IEEE-488.2 GPIB Remote Control	R) RS-232C Remote Control
D) Front Panel RF Connectors	S) Internal RF Switching Unit *)
E) RF Power Indication (digital) *)	U) USB Remote Control
F) Gain Adjustment *)	W) Liquid Cooling
G) Output Isolator *)	X) External Control of other Amplifiers
H) DC Supply	
I) 3x 208 V AC / 60 Hz	

*) These options may reduce output power and/or gain