

## STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 8012-1	8 ... 12 GHz	1 / 1.2	30 / 32 ±2	20 / 20	30	2 HU, 430 mm	9
BLMA 8012-2	8 ... 12 GHz	2 / 2.3	33 / 35 ±2	20 / 20	70	2 HU, 430 mm	10
BLMA 8012-4	8 ... 12 GHz	4 / 4.5	36 / 38 ±2	20 / 20	80	2 HU, 430 mm	10
BLMA 8012-5	8 ... 12 GHz	5 / 6	37 / 39 ±2	20 / 20	90	2 HU, 430 mm	11
BLMA 8012-10	8 ... 12 GHz	10 / 13	40 / 42 ±2	20 / 20	125	2 HU, 430 mm	11
BLMA 8012-15	8 ... 12 GHz	15 / 20	41.8 / 44 ±2	20 / 20	150	2 HU, 430 mm	12
BLMA 8012-20	8 ... 12 GHz	20 / 25	43 / 46 ±3	20 / 20	450	2 HU, 430 mm	12
BLMA 8012-25	8 ... 12 GHz	25 / 35	44 / 47 ±3	20 / 20	500	2 HU, 430 mm	17
BLMA 8012-40	8 ... 12 GHz	40 / 45	46 / 49 ±3	20 / 20	500	3 HU, 430 mm	17
BLMA 8012-80	8 ... 12 GHz	80 / 90	49 / 53 ±4	20 / 20	1000	3 HU, 430 mm	18
BLMA 8012-150	8 ... 12 GHz	150 / 160	51.8 / 55 ±3	20 / 20	2000	5 HU, 630 mm	48

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	$P_N$ -0.5 dB min. at VSWR 2:1
Spurious (at $P_N$ ):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear or AB-linear

## GENERAL

RF Input:	<12 GHz	N-f, standard on rear panel
	12 bis 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
RF Output:	<12 GHz	N-f, standard on rear panel
	12 to 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
Mains Supply:	Line Power:	
	Line Power	
	<800 VA	100 ... 240 V AC ±10%
	800 ... 3000 VA	200 ... 240 V AC ±10%
	>3000 VA	3x 400 V AC ±10%
Elapsed Time Meter:	via status display	

# BLMA 8 ... 12 GHz Solid State Amplifiers

<b>Ambient Temperature:</b>	0 ... +45 °C
<b>Storage Temperature:</b>	-20 ... +85 °C
<b>Relative Humidity:</b>	up to 95% (non-condensing)
<b>Operating Altitude:</b>	up to 2000 m above sea level
<b>Vibration and Shock:</b>	MIL-STD-810 F
<b>Cooling:</b>	forced air with integral blower air intake from front, air exhaust at rear

## OPTIONS

---

A) RF-Sample Ports *)	L) LAN Remote Control
B) External Dual Directional Coupler	N) Harmonics Filtering *)
C) IEEE-488.2 GPIB Remote Control	R) RS-232C Remote Control
D) Front Panel RF Connectors	S) Internal RF Switching Unit *)
E) RF Power Indication [digital] *)	U) USB Remote Control
F) Gain Adjustment *)	W) Liquid Cooling
G) Output Isolator *)	X) External Control of other Amplifiers
H) DC Supply	
I) 3x 208 V AC / 60 Hz	

\*) These options may reduce output power and/or gain