

## STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min dBm	Gain min / typ dB	Noise Figure dB	Dimensions (L, W, H) mm	Weight kg
BLMA 1826-2M	18 ... 26.5 GHz	+10	30 / 32 ±2	2.5	144 x 93 x 65	1

## STANDARD SPECIFICATIONS

Input Impedance:	50 Ohm nominal
Load VSWR:	<2.5:1 typ.
Spurious:	-50 dBc typ. (excluding harmonics)
Harmonics:	-20 dBc
Class of Operation:	A-linear

## GENERAL

RF Input:	SMA-f
RF Output:	SMA-f
Mains Supply:	210 ... 240 V AC, 47 ... 63 Hz
Power Consumption:	<10 W
Conformity:	CE (EN 55022, CISPR 22)
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G

## OPTIONS

-1A: CISPR, FCC, MIL, EN	for civil applications
-A: CISPR, FCC, MIL, EN	for basic laboratory measurements (economic)
-BT: (including filter)	Bluetooth for measurements of bluetooth systems
-M: MIL-461, MIL-285	for MIL-compliant measurements
K) Battery Operation	<sup>1)</sup> Bluetooth filter limits the useable frequency range to 3 ... 18 GHz!