

## STANDARD MODELS

Model	Frequency Range	Output Power P <sub>P</sub> min / Duty W / %	Pulse Width max. **)	Gain typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
TWAP 0818-1800	8 ... 18 GHz	1800 / 6	50 µs	68 ±5	6 / 20	1300	4 HU, 630 mm	30
TWAP 0818-1800L	8 ... 18 GHz	1800 / 6	50 µs	68 ±5	6 / 20	1300	6 HU, 800 mm	48
TWAP 0818-2000	8 ... 18 GHz	2000 / 4	50 µs	68 ±6	7 / 18	1300	4 HU, 630 mm	33
TWAP 0818-2000L	8 ... 18 GHz	2000 / 4	50 µs	68 ±6	7 / 18	1300	6 HU, 800 mm	48
TWAP 0818-2500	8 ... 18 GHz	2500 / 6	50 µs	72 ±7.5	7 / 15	2000	8 HU, 630 mm	50
TWAP 0818-3000	8 ... 18 GHz	3000 / 6	50 µs	74 ±7.5	8 / 10	3000	12 HU, 800 mm	108

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	P <sub>N</sub> -0.5 dB min. at VSWR 2:1
P-RF:	100 kHz max.
Spurious (at P <sub>N</sub> ):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear

## GENERAL

RF Input:	<8 GHz	N-f, standard on rear panel
	8 to 18 GHz	SMA-f, standard on front panel
	>18 GHz	2.92 mm-f, standard on front panel
RF Output:	<8 GHz	7-16-f, standard on rear panel
	4 to 8 GHz	WRD 350, standard on rear panel
	8 to 12 GHz	WR 90, standard on rear panel
	8 to 18 GHz	WRD 750, standard on rear panel
	12 to 18 GHz	WR 62, standard on rear panel
Mains Supply:	PLine up to 3 kVA	200 ... 240 V AC
	PLine >3 kVA	3x 400 V AC
Elapsed Time Meter:	via status display	
Ambient Temperature:	0 ... +45 °C	
Storage Temperature:	-20 ... +85 °C	
Relative Humidity:	up to 95% (non-condensing)	
Operating Altitude:	up to 2000 m above sea level	
Vibration and Shock:	MIL-STD-810 G	
Cooling:	forced air with integral blower	
	air intake from front, air exhaust at rear	

## OPTIONS

---

- |                                      |   |
|--------------------------------------|---|
| A) Sample Ports *)                   | L) LAN Remote Control                   |
| B) External Dual Directional Coupler | R) RS-232C Remote Control               |
| C) IEEE-488.2 GPIB Remote Control    | S) Internal RF Switching Unit *)        |
| D) Front Panel RF Connectors         | U) USB Remote Control                   |
| E) RF Power Indication (digital) *)  | W) Liquid Cooling                       |
| F) Gain Adjustment *)                | X) External Control of other Amplifiers |
| G) Output Isolator *)                |   |
| H) DC Supply                         |   |
| I) 3x 208 V AC / 60 Hz               |   |
| J) 100 V AC                          |   |

\*) These options may reduce output power and/or gain

\*\*) Optionally other pulse width available