

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0125-5	9 kHz ... 250 MHz	5 / 8	37 / 39 ±2	20 / 20	100	2 HU, 430 mm	10
BSA 0125-15	9 kHz ... 250 MHz	15 / 25	41.8 / 44 ±2	20 / 20	175	2 HU, 430 mm	12
BSA 0125-25	9 kHz ... 250 MHz	25 / 30	44 / 46 ±2	20 / 20	300	2 HU, 430 mm	12
BSA 0125-75	9 kHz ... 250 MHz	75 / 100	48.8 / 51 ±2	25 / 20	350	2 HU, 430 mm	13
BSA 0125-125	9 kHz ... 250 MHz	125 / 150	51 / 53 ±2	20 / 20	550	2 HU, 430 mm	14
BSA 0125-150	9 kHz ... 250 MHz	150 / 200	51.8 / 54 ±2	20 / 20	650	3 HU, 630 mm	27
BSA 0125-200	9 kHz ... 250 MHz	200 / 220	53 / 55 ±2	20 / 20	1150	3 HU, 630 mm	30
BSA 0125-250	9 kHz ... 250 MHz	250 / 300	54 / 56 ±2	20 / 20	1300	3 HU, 630 mm	31
BSA 0125-300N	9 kHz ... 250 MHz	300 / 350	54 / 56 ±2	20 / 20	850	3 HU, 630 mm	34
BSA 0125-400	9 kHz ... 250 MHz	400 / 500	56 / 58 ±2	20 / 20	2000	5 HU, 630 mm	52
BSA 0125-500	9 kHz ... 250 MHz	500 / 600	57 / 59 ±2	20 / 20	2800	5 HU, 630 mm	58
BSA 0125-800	9 kHz ... 250 MHz	800 / 900	59 / 61 ±2	20 / 20	3500	5 HU, 630 mm	62
BSA 0125-1000/800	9 kHz ... 250 MHz				6000	10 HU, 630 mm	110
	9 kHz ... 200 MHz	1000 / 1200	60 / 62 ±2	20 / 18			
	200 ... 250 MHz	800 / 1000	59 / 61 ±2	20 / 20			
BSA 0125-1000	9 kHz ... 250 MHz	1000 / 1100	60 / 62 ±2	20 / 18	7000	10 HU, 630 mm	110
BSA 0125-1250	9 kHz ... 250 MHz	1250 / 1350	61 / 63 ±2	20 / 18	7500	10 HU, 630 mm	110
BSA 0125-2000	9 kHz ... 250 MHz	2000 / 2200	63 / 65 ±2	20 / 18	14000	18 HU, 800 mm	180

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	P_N -0.5 dB min. at VSWR 2:1
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A linear or A-B linear

GENERAL

RF Input:	N-f, standard on rear panel	
RF Output:	standard on rear panel	
	<1 kW	N-f
	<3 kW	7-16-f
	<5 kW	EIA 1 5/8
Mains Supply:	Line Power:	
	<1000 VA	100 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz
	1000 ... 3000 VA	200 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz
	>3000 VA	3x 400 V AC $\pm 10\%$ / 47 ... 63 Hz
Elapsed Time Meter:	via status display	
Ambient Temperature:	0 ... +45 °C	
Storage Temperature:	-20 ... +85 °C	
Relative Humidity:	up to 95% (non-condensing)	
Operating Altitude:	up to 2000 m above sea level	
Vibration and Shock:	MIL-STD-810 G	
Cooling:	forced air with integral blower air intake from front, air exhaust at rear	

OPTIONS

A) RF Monitor Outputs	L) LAN Remote Control
B) External Dual Directional Coupler	R) RS-232C Remote Control
C) IEEE-488.2 GPIB Remote Control	S) Internal RF Switching Unit
D) Front Panel RF Connectors	U) USB Remote Control
E) RF Power Indication (digital)	W) Liquid Cooling
F) Gain Adjustment	X) External Control of other Amplifiers
H) DC Supply	