

STANDARDMODELLE

Modell	Frequenzbereich	Ausgangsleistung $P_N$ min dBm	Verstärkung min / typ dB	Rauschzahl dB	Abmessungen (L, B, H) mm	Gewicht kg
BLMA 1840-1M	18 ... 40 GHz	+5	23 / 26 ±2,5	2,7	120 x 100 x 51	1
BLMA 1840-1A	18 ... 40 GHz	+5	23 / 26 ±2,5	3	120 x 100 x 51	1
BLMA 1840-2A	18 ... 40 GHz	+5	23 / 26 ±2,5	3,5	120 x 100 x 51	1
BLMA 1840-3A	18 ... 40 GHz	+5	23 / 26 ±2,5	5	120 x 100 x 51	1
BLMA 1840-3G	18 ... 40 GHz	+5	30 / 33 ±2,5	2,9	120 x 100 x 51	1
BLMA 1840-4G	18 ... 40 GHz	+5	42 / 45 ±2,5	3	120 x 100 x 51	1
BLMA 1840-4A	18 ... 40 GHz	+5	32 / 35 ±2,5	2,8	120 x 100 x 51	1
BLMA 1840-5G	18 ... 40 GHz	+5	46 / 49 ±2,5	3	120 x 100 x 51	1