

## STANDARD MODELS

Model	Frequency Range	Output Power P <sub>P</sub> min / Duty W pk / %	Pulse Width max. **)	Gain typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BPA 1114-900	1150 ... 1450 MHz	900 / 10	100	62 ±2.5	30 / 30	500	3 HU, 630 mm	22

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant) P <sub>N</sub> -0.5 dB min. at VSWR 2:1
Pulse Droop:	1.0 dB
Spurious (at P <sub>N</sub> ):	-50 dBc typ. (excluding harmonics)
Class of Operation:	C

## GENERAL

RF Input:	<8 GHz	N-f, standard on rear panel
	8 to 18 GHz	SMA-f, standard on front panel
	> 18 GHz	K-f, standard on front panel
RF Output:	<8 GHz	N-f, standard on rear panel
	8 to 18 GHz	SMA-f, standard on front panel
	>18 GHz	K-f, standard on front panel
Mains Supply:	P <sub>P</sub> up to 100 W	85 ... 264 V AC
	P <sub>P</sub> >100 W	3x 400 V AC
Elapsed Time Meter:	via status display	
Ambient Temperature:	0 ... +45 °C	
Storage Temperature:	-20 ... +85 °C	
Relative Humidity:	up to 95% (non-condensing)	
Operating Altitude:	up to 2000 m above sea level	
Vibration and Shock:	MIL-STD-810 G	
Cooling:	forced air with integral blower	
	air intake from front, air exhaust at rear	

## OPTIONS

A) Sample Ports *)	R) RS-232C Remote Control
B) External Dual Directional Coupler	S) Internal RF Switching Unit *)
C) IEEE-488.2 GPIB Remote Control	U) USB Remote Control
D) Front Panel RF-Connectors	W) Liquid Cooling
E) RF Power Indication (digital) *)	X) External Control of other Amplifiers
F) Gain Adjustment *)	
G) Output Isolator *)	

\*) These options may reduce output power and/or gain

# BPA 1.15 ... 1.45 GHz Pulsed Solid State Amplifiers

H) DC-Supply

I) 3x 208 V AC / 60 Hz

L) LAN Remote Control

\*\*) Optionally other pulse width available