

STANDARD MODELS

Model	Frequency Range	Output Power P _P min / Duty W pk / %	Pulse Width max. **)	Gain typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BPA 1214-500	1.2 ... 1.4 GHz	500 / 10	100 µs	57 ±2.5	30 / 30	250	2 HU, 430 mm	14
BPA 1214-1000	1.2 ... 1.4 GHz	1000 / 10	100 µs	60 ±2.5	30 / 30	500	3 HU, 630 mm	22
BPA 1214-1800	1.2 ... 1.4 GHz	1800 / 10	100 µs	63 ±2.5	30 / 30	1000	4 HU, 630 mm	35
BPA 1214-3000	1.2 ... 1.4 GHz	3000 / 10	100 µs	65 ±2.5	30 / 30	1500	6 HU, 630 mm	35
BPA 1214-5000	1.2 ... 1.4 GHz	5000 / 10	100 µs	67 ±2.5	30 / 30	3000	8 HU, 630 mm	60

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant) P _N -0.5 dB min. at VSWR 2:1
Pulse Droop:	1.0 dB
Spurious (at P _N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	C

GENERAL

RF Input:	<8 GHz	N-f, standard on rear panel
	8 to 18 GHz	SMA-f, standard on front panel
	> 18 GHz	K-f, standard on front panel
RF Output:	<8 GHz	N-f, standard on rear panel
	8 to 18 GHz	SMA-f, standard on front panel
	>18 GHz	K-f, standard on front panel
Mains Supply:	P _P up to 100 W	85 ... 264 V AC
	P _P >100 W	3x 400 V AC
Elapsed Time Meter:	via status display	
Ambient Temperature:	0 ... +45 °C	
Storage Temperature:	-20 ... +85 °C	
Relative Humidity:	up to 95% (non-condensing)	
Operating Altitude:	up to 2000 m above sea level	
Vibration and Shock:	MIL-STD-810 F	
Cooling:	forced air with integral blower air intake from front, air exhaust at rear	

BPA 1.2 ... 1.4 GHz Pulsed Solid State Amplifiers

OPTIONS

- | | |
|--------------------------------------|---|
| A) Sample Ports *) | R) RS-232C Remote Control |
| B) External Dual Directional Coupler | S) Internal RF Switching Unit *) |
| C) IEEE-488.2 GPIB Remote Control | U) USB Remote Control |
| D) Front Panel RF-Connectors | W) Liquid Cooling |
| E) RF Power Indication (digital) *) | X) External Control of other Amplifiers |
| F) Gain Adjustment *) | |
| G) Output Isolator *) | |
| H) DC-Supply | |
| I) 3x 208 V AC / 60 Hz | |
| L) LAN Remote Control | |

*) These options may reduce output power and/or gain

**) Optionally other pulse width available