

## STANDARD MODELS

| Model          | Frequency Range   | Output Power<br>$P_N$ min / typ<br>W | Gain<br>min / typ<br>dB | Harmonics<br>2nd / 3rd<br>dBc | Line Power<br>VA | Dimensions<br>(H, D)<br>19"-System | Weight<br>kg |
|----------------|-------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BSA 0122-5000W | 9 kHz ... 225 MHz | 5000 / 5500                          | 67 / 70 ±3              | 20 / 20                       | 30000            | 37 HU, 800 mm (XL)                 | 600          |

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

|                       |   |
|-----------------------|---|
| Input Power:          | 0 dBm (1 mW) max.                               |
| Overdrive Protection: | up to +10 dBm for no damage                     |
| Input Impedance:      | 50 Ohm nominal                                  |
| Output Impedance:     | 50 Ohm nominal                                  |
| Input VSWR:           | <2:1 typ.                                       |
| Load VSWR:            | infinite for no damage (100% mismatch tolerant) |
|                       | $P_N$ -0.5 dB min. at VSWR 2:1                  |
| Spurious (at $P_N$ ): | -50 dBc typ. (excluding harmonics)              |
| Class of Operation:   | A-linear  |

## GENERAL

|                      |   |
|----------------------|---|
| RF Input:            | N-f, standard on rear panel   |
| RF Output:           | 1 5/8, standard on rear panel   |
| Mains Supply:        | 3x 400 V AC ±10%, 47 ... 63 Hz  |
| Elapsed Time Meter:  | via status display  |
| Ambient Temperature: | 0 ... +45 °C  |
| Storage Temperature: | -20 ... +85 °C  |
| Relative Humidity:   | up to 95% (non-condensing)  |
| Operating Altitude:  | up to 2000 m above sea level  |
| Vibration and Shock: | MIL-STD-810 G   |
| Cooling:             | forced air with integral blower<br>air intake from front, air exhaust at rear<br>Option W: Liquid cooling<br>External heat exchanger required |

## OPTIONS

|                                      |   |
|--------------------------------------|---|
| A) RF Monitor Outputs                | L) LAN Remote Control                   |
| B) External Dual Directional Coupler | R) RS-232C Remote Control               |
| C) IEEE-488.2 GPIB Remote Control    | S) Internal RF Switching Unit           |
| D) Front Panel RF Connectors         | U) USB Remote Control                   |
| E) RF Power Indication (digital)     | W) Liquid Cooling                       |
| F) Gain Adjustment                   | X) External Control of other Amplifiers |
| H) DC Supply                         | (XL) Rack width 800 mm                  |