

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 0860-10D	80 ... 6000 MHz				270	2 HU, 430 mm	15
	80 ... 1000 MHz	10 / 12	40 / 42 ±2	20 / 20			
	1000 ... 6000 MHz	10 / 12	40 / 42 ±2	15 / 20			
BLWA 0860-30D	80 ... 6000 MHz				500	3 HU, 430 mm	15
	80 ... 1000 MHz	30 / 35	44.8 / 47 ±2	20 / 20			
	1000 ... 6000 MHz	30 / 35	44.8 / 47 ±2	15 / 20			
BLWA 0860-50/20D	80 ... 6000 MHz				700	3 HU, 430 mm	18
	80 ... 1000 MHz	50 / 60	47 / 49 ±2	20 / 20			
	1000 ... 6000 MHz	20 / 30	43 / 46 ±3	15 / 20			
BLWA 0860-150D	80 ... 6000 MHz				2100	6 HU, 630 mm	64
	80 ... 1000 MHz	150 / 180	51.8 / 54 ±2	20 / 20			
	1000 ... 6000 MHz	150 / 180	51.8 / 55 ±3	15 / 20			
BLWA 0860-200/100/50D	80 ... 6000 MHz				1400	4 HU, 630 mm	37
	80 ... 400 MHz	200 / 250	53 / 55 ±2	20 / 20			
	400 ... 2500 MHz	100 / 120	50 / 53 ±3	15 / 20			
	2500 ... 6000 MHz	50 / 55	47 / 50 ±3	15 / 20			
BLWA 0860-200/100D	80 ... 6000 MHz				1900	5 HU, 630 mm	58
	80 ... 1000 MHz	200 / 250	53 / 55 ±2	20 / 20			
	1000 ... 6000 MHz	100 / 120	50 / 53 ±3	15 / 20			
BLWA 0860-250/100D	80 ... 6000 MHz				2050	6 HU, 630 mm	62
	80 ... 1000 MHz	250 / 300	54 / 56 ±2	20 / 20			
	1000 ... 6000 MHz	100 / 120	50 / 53 ±3	15 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	P_N -0.5 dB min. at VSWR 2:1
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A linear or A-B linear

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	standard on rear panel
	P_N up to 1 kW N-f
	P_N >1 kW 7-16-f
	P_N >2 kW 13-30-f or 1 5/8" EIA
Mains Supply:	Line Power:
	<1000 VA 100 ... 240 V AC \pm 10%
	1000 ... 3000 VA 200 ... 240 V AC \pm 10%
	>3000 VA 3x 400 V AC \pm 10%
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

OPTIONS

A) RF-Sample Ports	I) 3x 208 V AC / 60 Hz
B) External Dual Directional Coupler	L) LAN Remote Control
C) IEEE-488.2 GPIB Remote Control	S) Internal RF Switching Unit
D) Front Panel RF Connectors	R) RS-232C Remote Control
E) RF Power Indication (digital)	U) USB Remote Control
F) Gain Adjustment	W) Liquid Cooling
H) DC Supply	X) External Control of other Amplifiers