

**STANDARD MODELS**

| Model           | Frequency Range | Power<br>CW min<br>W | Attenuation<br>nom / Variation<br>dB | VSWR<br>max | Input<br>Connector | Output<br>Connector | Dimensions<br>(L, W, H)<br>mm | Weight<br>kg | Part<br>Number |
|-----------------|-----------------|----------------------|--------------------------------------|-------------|--------------------|---------------------|-------------------------------|--------------|----------------|
| BCA 0018-20/25  | DC ... 18 GHz   | 25                   | 20±0.75                              | 1.35:1      | N-m                | N-f                 | 46 / 38.1 / 38.1              | 0.11         | 10021877       |
| BCA 0018-20/50  | DC ... 18 GHz   | 50                   | 20±0.75                              | 1.35:1      | N-m                | N-f                 | 101.7 / 38.1 / 38.1           | 0.21         | 10021878       |
| BCA 0018-30/500 | DC ... 18 GHz   | 500                  | 30±3                                 | 1.5:1       | N-m                | N-f                 | 509 / 110 / 120               | 6            | 10020635       |
| BCA 0018-40/100 | DC ... 18 GHz   | 100                  | 40±0.75                              | 1.45:1      | N-m                | N-f                 | 211 / 38.1 / 38.1             | 7.4          | 10020636       |

For individual data sheets, please click on the above model name

Dimensions without connectors