

STANDARDMODELLE

Modell	Frequenzbereich X)	Kopplung X) dB	Leistung P _{min} W	Dämpfung max dB	Richtschärfe min dB	VSWR max Hauptarm	Hauptarm Stecker 1), 2)	Koppelarm Stecker 3)
BDC 1080-20/200	1 ... 8 GHz	20 ±1	200	0,3	20	1.4:1	N-f	SMA-f


S: Einzel-Richtkoppler

OPTIONEN

- 1) Männlicher Stecker am HF-Eingang
- 2) Andere Steckerart am Hauptarm
- 3) N-f Stecker an den Koppelports
- X) Spezielle Frequenzbereiche und Koppeldämpfungen auf Anfrage

Dieses Dokument ist Eigentum der Firma Bonn Elektronik GmbH.
Vervielfältigung und Veröffentlichung ohne ausdrückliche Genehmigung ist untersagt. Änderungen im
Sinne des technischen Fortschritts können ohne Vorankündigungen vorgenommen werden. Wenn
nichts anders angegeben alle Maße Millimeter.

This document is the property of Bonn Elektronik GmbH.
Reproduction and release without express permission is strictly prohibited.
We reserve the right to introduce modifications without prior notification, where they serve
technical progress. Unless otherwise indicated all dimensions millimeters.



Product Information		Entwurf
10018253		26.02.19 Bonn
Directional Coupler		Zeichnung
BDC 1080-20/200		26.02.19 Bhu
BONN Elektronik  info@bonn-elektronik.com • www.bonn-elektronik.com		Prüfung
		26.02.19 Maleta
1-1		Freigabe
		26.02.19 Bonn