

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 0250-15	20 ... 500 MHz	15 / 18	41.8 / 44 ±2	20 / 15	250	2 HU, 430 mm	12
BLWA 0250-35	20 ... 500 MHz	35 / 40	45.4 / 48 ±2	20 / 20	280	2 HU, 430 mm	13
BLWA 0250-60	20 ... 500 MHz	60 / 70	47.8 / 50 ±2	20 / 15	350	2 HU, 430 mm	13
BLWA 0250-85	20 ... 500 MHz	85 / 100	49.3 / 52 ±2	20 / 15	500	3 HU, 430 mm	18
BLWA 0250-125	20 ... 500 MHz	125 / 135	51 / 53 ±2	20 / 20	1000	3 HU, 630 mm	35
BLWA 0250-250	20 ... 500 MHz	250 / 300	54 / 56 ±2	20 / 20	1250	4 HU, 630 mm	40
BLWA 0250-500	20 ... 500 MHz	500 / 600	57 / 59 ±2	20 / 20	3000	4 HU, 630 mm	45
BLWA 0250-750	20 ... 500 MHz	750 / 800	58.8 / 61 ±2	20 / 20	4500	8 HU, 630 mm	80
BLWA 0250-1000	20 ... 500 MHz	1000 / 1200	60 / 62 ±2	20 / 20	6500	9 HU, 630 mm	95
BLWA 0250-1500	20 ... 500 MHz	1500 / 1650	61.8 / 64 ±2	20 / 20	9000	15 HU, 630 mm	160
BLWA 0250-2000	20 ... 500 MHz	2000 / 2500	63 / 65 ±2	20 / 20	13000	18 HU, 800 mm	185
BLWA 0250-3000	20 ... 500 MHz	3000 / 3500	64.8 / 67 ±2	20 / 20	18000	37 HU, 800 mm	310

For individual data sheets, please click on the above model name

1 HU = 44.45 mm