

STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 0525-10	0.5 ... 2.5 GHz	10 / 12	40 / 42 ±2	20 / 20	120	2 HU, 430 mm	10
BLMA 0525-20	0.5 ... 2.5 GHz	20 / 30	43 / 45 ±2	12 / 15	150	2 HU, 430 mm	12
BLMA 0525-35	0.5 ... 2.5 GHz	35 / 50	45.4 / 48 ±2	15 / 20	300	2 HU, 430 mm	13
BLMA 0525-50	0.5 ... 2.5 GHz	50 / 60	47 / 49 ±2	15 / 20	470	2 HU, 430 mm	13
BLMA 0525-75	0.5 ... 2.5 GHz	75 / 100	48.8 / 51 ±2	12 / 20	500	3 HU, 430 mm	19
BLMA 0525-100	0.5 ... 2.5 GHz	100 / 120	50 / 52 ±2	15 / 20	800	3 HU, 430 mm	22
BLMA 0525-150	0.5 ... 2.5 GHz	150 / 180	51.5 / 54 ±2	15 / 20	1000	3 HU, 630 mm	26
BLMA 0525-200	0.5 ... 2.5 GHz	200 / 220	53 / 56 ±3	15 / 20	1500	4 HU, 630 mm	36
BLMA 0525-250	0.5 ... 2.5 GHz	250 / 300	54 / 56 ±2	15 / 20	2000	4 HU, 630 mm	39
BLMA 0525-400	0.5 ... 2.5 GHz	400 / 450	56 / 59 ±3	15 / 20	3000	6 HU, 630 mm	62
BLMA 0525-500	0.5 ... 2.5 GHz	500 / 600	57 / 59 ±2	15 / 20	3500	8 HU, 630 mm	88
BLMA 0525-750	0.5 ... 2.5 GHz	750 / 800	58.8 / 61 ±2	15 / 20	6000	15 HU, 630 mm	135
BLMA 0525-1600	0.5 ... 2.5 GHz	1500 / 1600	61.8 / 64 ±2	15 / 20	12000	37 HU, 800 mm	275

For individual data sheets, please click on the above model name

1 HU = 44.45 mm