

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 1030-1	1 ... 3 GHz	1 / 1.3	30 / 32 ±2	20 / 20	50	2 HU, 430 mm	11
BLMA 1030-3	1 ... 3 GHz	3 / 3.5	34.8 / 37 ±2	20 / 20	75	2 HU, 430 mm	12
BLMA 1030-5	1 ... 3 GHz	5 / 6	37 / 39 ±2	20 / 20	75	2 HU, 430 mm	12
BLMA 1030-10	1 ... 3 GHz	10 / 13	40 / 43 ±3	20 / 20	110	2 HU, 430 mm	12
BLMA 1030-20	1 ... 3 GHz	20 / 25	43 / 45 ±2	15 / 20	270	2 HU, 430 mm	12
BLMA 1030-40	1 ... 3 GHz	40 / 50	46 / 48 ±2	15 / 20	280	2 HU, 430 mm	13
BLMA 1030-80	1 ... 3 GHz	80 / 100	49 / 51 ±2	20 / 20	450	3 HU, 430 mm	18
BLMA 1030-100	1 ... 3 GHz	100 / 120	50 / 52 ±2	18 / 20	500	3 HU, 430 mm	17
BLMA 1030-150	1 ... 3 GHz	150 / 200	51.8 / 54 ±2	15 / 20	1600	3 HU, 630 mm	24
BLMA 1030-200	1 ... 3 GHz	200 / 230	53 / 55 ±2	20 / 20	1800	4 HU, 630 mm	38
BLMA 1030-250	1 ... 3 GHz	250 / 300	54 / 56 ±2	20 / 20	1800	4 HU, 630 mm	39
BLMA 1030-300	1 ... 3 GHz	300 / 330	54.8 / 57 ±2	20 / 20	1800	4 HU, 630 mm	42
BLMA 1030-500	1 ... 3 GHz	500 / 550	57 / 59 ±2	20 / 20	3800	8 HU, 630 mm	91
BLMA 1030-800	1 ... 3 GHz	800 / 850	59 / 62 ±3	15 / 20	6000	8 HU, 630 mm	92
BLMA 1030-1000	1 ... 3 GHz	1000 / 1200	60 / 63 ±3	15 / 20	10000	12 HU, 630 mm	130

For individual data sheets, please click on the above model name

1 HU = 44.45 mm