

STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 0210-1	20 ... 1000 MHz	1 / 1.5	30 / 32 ±2	20 / 20	75	2 HU, 430 mm	11
BLWA 0210-3	20 ... 1000 MHz	3 / 3.5	34.8 / 37 ±2	20 / 20	100	2 HU, 430 mm	11
BLWA 0210-5	20 ... 1000 MHz	5 / 6	37 / 39 ±2	20 / 20	150	2 HU, 430 mm	12
BLWA 0210-10	20 ... 1000 MHz	10 / 12	40 / 42 ±2	20 / 20	200	2 HU, 430 mm	12
BLWA 0210-30	20 ... 1000 MHz	30 / 35	44.8 / 47 ±2	20 / 20	230	2 HU, 430 mm	12
BLWA 0210-40	20 ... 1000 MHz	40 / 45	46 / 48 ±2	20 / 20	300	2 HU, 430 mm	13
BLWA 0210-50	20 ... 1000 MHz	50 / 60	48 / 50 ±2	20 / 20	330	2 HU, 430 mm	13
BLWA 0210-100	20 ... 1000 MHz	100 / 120	50 / 52 ±2	20 / 20	900	3 HU, 630 mm	26
BLWA 0210-150	20 ... 1000 MHz	150 / 200	51.8 / 54 ±2	20 / 20	2100	4 HU, 630 mm	40
BLWA 0210-300	20 ... 1000 MHz	300 / 330	54.8 / 57 ±2	20 / 15	3000	4 HU, 630 mm	42
BLWA 0210-500	20 ... 1000 MHz	500 / 550	57 / 59 ±2	20 / 15	4000	8 HU, 630 mm	58
BLWA 0210-350/200/100D	20 ... 1000 MHz				1000	8 HU, 630 mm	60
	20 ... 100 MHz	350 / 400	55.4 / 58 ±2	20 / 15			
	100 ... 400 MHz	200 / 220	53 / 55 ±2	20 / 15			
	400 ... 1000 MHz	100 / 120	50 / 52 ±2	20 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm