

STANDARD MODELS

| Model | Frequency Range | Output Power P_N min / typ W | Gain min / typ dB | Harmonics 2nd / 3rd dBc | Line Power VA | Dimensions (H, D) 19"-System | Weight kg |
|------------------------|------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BLWA 0210-1 | 20 ... 1000 MHz | 1 / 1.5 | 30 / 32 ±2 | 20 / 20 | 75 | 2 HU, 430 mm | 11 |
| BLWA 0210-3 | 20 ... 1000 MHz | 3 / 3.5 | 34.8 / 37 ±2 | 20 / 20 | 100 | 2 HU, 430 mm | 11 |
| BLWA 0210-5 | 20 ... 1000 MHz | 5 / 6 | 37 / 39 ±2 | 20 / 20 | 120 | 2 HU, 430 mm | 12 |
| BLWA 0210-10 | 20 ... 1000 MHz | 10 / 12 | 40 / 42 ±2 | 20 / 20 | 130 | 2 HU, 430 mm | 12 |
| BLWA 0210-30 | 20 ... 1000 MHz | 30 / 35 | 44.8 / 47 ±2 | 20 / 20 | 230 | 2 HU, 430 mm | 12 |
| BLWA 0210-40 | 20 ... 1000 MHz | 40 / 45 | 46 / 48 ±2 | 20 / 20 | 300 | 2 HU, 430 mm | 13 |
| BLWA 0210-50 | 20 ... 1000 MHz | 50 / 60 | 48 / 50 ±2 | 20 / 20 | 330 | 2 HU, 430 mm | 13 |
| BLWA 0210-100 | 20 ... 1000 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | 900 | 3 HU, 630 mm | 26 |
| BLWA 0210-150 | 20 ... 1000 MHz | 150 / 200 | 51.8 / 54 ±2 | 20 / 20 | 2100 | 4 HU, 630 mm | 40 |
| BLWA 0210-300 | 20 ... 1000 MHz | 300 / 330 | 54.8 / 57 ±2 | 20 / 15 | 3000 | 4 HU, 630 mm | 42 |
| BLWA 0210-500 | 20 ... 1000 MHz | 500 / 550 | 57 / 59 ±2 | 20 / 15 | 4000 | 8 HU, 630 mm | 58 |
| BLWA 0210-350/200/100D | 20 ... 1000 MHz | | | | 1000 | 8 HU, 630 mm | 60 |
| | 20 ... 100 MHz | 350 / 400 | 55.4 / 58 ±2 | 20 / 15 | | | |
| | 100 ... 400 MHz | 200 / 220 | 53 / 55 ±2 | 20 / 15 | | | |
| | 400 ... 1000 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | | | |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm