

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 0840-150	80 ... 400 MHz	150 / 180	51.8 / 54 ±2	20 / 15	800	3 HU, 630 mm	30
BLWA 0840-250	80 ... 400 MHz	250 / 300	54 / 56 ±2	20 / 15	1600	4 HU, 630 mm	35
BLWA 0840-500	80 ... 400 MHz	500 / 600	57 / 59 ±2	20 / 15	3000	6 HU, 630 mm	55
BLWA 0840-750	80 ... 400 MHz	750 / 900	58.8 / 61 ±2	20 / 15	4500	8 HU, 630 mm	120
BLWA 0840-1000	80 ... 400 MHz	1000 / 1150	60 / 62 ±2	20 / 15	8000	16 HU, 630 mm	180
BLWA 0840-1500	80 ... 400 MHz	1500 / 1700	61.8 / 64 ±2	20 / 15	10000	19 HU, 630 mm	200
BLWA 0840-2000	80 ... 400 MHz	2000 / 2200	63 / 65 ±2	20 / 15	17000	41 HU, 800 mm	300
BLWA 0840-3000	80 ... 400 MHz	3000 / 3300	64.8 / 67 ±2	20 / 15	20000	41 HU, 800 mm	400
BLWA 0840-4000	80 ... 400 MHz	4000 / 4400	66 / 68 ±2	20 / 15	35000	2x 37 HU, 800 mm	600
BLWA 0840-5000	80 ... 400 MHz	5000 / 5500	67 / 69 ±2	20 / 15	45000	2x 37 HU, 800 mm	800

For individual data sheets, please click on the above model name

1 HU = 44.45 mm