

STANDARD MODELS

| Model | Frequency Range | Output Power P_N min / typ W | Gain min / typ dB | Harmonics 2nd / 3rd dBc | Line Power VA | Dimensions (H, D) 19"-System | Weight kg |
|-----------------------|-------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BLWA 0825-250/100/35D | 80 ... 2500 MHz | | | | 1200 | 4 HU, 630 mm | 38 |
| | 80 ... 400 MHz | 250 / 300 | 54 / 56 ±2 | 20 / 15 | | | |
| | 400 ... 1000 MHz | 100 / 150 | 50 / 52 ±2 | 20 / 20 | | | |
| | 1000 ... 2500 MHz | 35 / 40 | 45.4 / 48 ±2 | 20 / 20 | | | |

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

| | |
|-----------------------|---|
| Input Power: | 0 dBm (1 mW) max. |
| Overdrive Protection: | up to +10 dBm for no damage |
| Input Impedance: | 50 Ohm nominal |
| Output Impedance: | 50 Ohm nominal |
| Input VSWR: | <2:1 typ. |
| Load VSWR: | infinite for no damage (100% mismatch tolerant) |
| | P_N -0.5 dB min. at VSWR 2:1 |
| Spurious (at P_N): | -60 dBc min. (excluding harmonics) |
| Class of Operation: | A-linear or AB-linear |

GENERAL

| | |
|----------------------|---|
| RF Input: | N-f, standard on rear panel |
| RF Output: | N-f, standard on rear panel |
| Mains Supply: | 100 ... 240 V AC, 47 ... 63 Hz |
| Elapsed Time Meter: | via status display |
| Ambient Temperature: | 0 ... +45 °C |
| Storage Temperature: | -25 ... +85 °C |
| Relative Humidity: | up to 95% (non-condensing) |
| Operating Altitude: | up to 2000 m above sea level |
| Vibration and Shock: | MIL-STD-810 G |
| Cooling: | forced air with integral blower air intake from front, air exhaust at rear Option W: Liquid cooling External heat exchanger required |

OPTIONS

| | |
|--------------------------------------|---|
| A) RF-Sample Ports | L) LAN Remote Control |
| B) External Dual Directional Coupler | P) Precise RMS RF Power Sensor (internal) |

BLWA 80 ... 2500 MHz Solid State Amplifiers

C) IEEE-488.2 GPIB Remote Control
D) Front Panel RF Connectors
E) RF Power Indication (digital)
F) Gain Adjustment
H) DC Supply
I) 3x 208 V AC / 60 Hz

R) RS-232C/RS-485 Remote Control
S) Internal RF Switching Unit
U) USB Remote Control
W) Liquid Cooling
X) External Control of other Amplifiers