

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 2050-100	200 ... 500 MHz	100 / 120	50 / 52 ±2	20 / 15	400	3 HU, 430 mm	19
BLWA 2050-150	200 ... 500 MHz	150 / 180	51.8 / 54 ±2	20 / 15	800	3 HU, 430 mm	24
BLWA 2050-300	200 ... 500 MHz	300 / 330	54.8 / 57 ±2	20 / 20	1500	3 HU, 630 mm	35
BLWA 2050-500	200 ... 500 MHz	500 / 600	57 / 59 ±2	20 / 20	2500	5 HU, 630 mm	43
BLWA 2050-750	200 ... 500 MHz	750 / 850	58.8 / 61 ±2	20 / 20	4000	6 HU, 630 mm	80
BLWA 2050-1000	200 ... 500 MHz	1000 / 1150	60 / 62 ±2	20 / 20	6000	9 HU, 630 mm	95
BLWA 2050-1500	200 ... 500 MHz	1500 / 1700	61.8 / 64 ±2	20 / 20	8000	16 HU, 630 mm	180
BLWA 2050-2000	200 ... 500 MHz	2000 / 2200	63 / 65 ±2	20 / 20	10000	19 HU, 630 mm	200
BLWA 2050-2500	200 ... 500 MHz	2500 / 2700	64 / 66 ±2	20 / 20	17000	41 HU, 800 mm	300
BLWA 2050-3500	200 ... 500 MHz	3500 / 4000	65.4 / 68 ±2	20 / 20	20000	41 HU, 800 mm	400
BLWA 2050-4500	200 ... 500 MHz	4500 / 5000	65.5 / 68 ±2	20 / 20	35000	2x 37 HU, 800 mm	600
BLWA 2050-6000	200 ... 500 MHz	6000 / 6500	67.8 / 70 ±2	20 / 20	45000	2x 37 HU, 800 mm	600

For individual data sheets, please click on the above model name

1 HU = 44.45 mm