

STANDARD MODELS

| Model | Frequency Range | Output Power P_N min / typ W | Gain min / typ dB | Harmonics 2nd / 3rd dBc | Line Power VA | Dimensions (H, D) 19"-System | Weight kg |
|----------------------|-------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BSA 0150-5 | 9 kHz ... 500 MHz | 5 / 8 | 37 / 39 ±2 | 20 / 20 | 100 | 2 HU, 430 mm | 11 |
| BSA 0150-10 | 9 kHz ... 500 MHz | 10 / 12 | 40 / 42 ±2 | 20 / 20 | 150 | 2 HU, 430 mm | 12 |
| BSA 0150-25 | 9 kHz ... 500 MHz | 25 / 30 | 44 / 46 ±2 | 20 / 20 | 200 | 2 HU, 430 mm | 12 |
| BSA 0150-30 | 9 kHz ... 500 MHz | 30 / 35 | 44.8 / 47 ±2 | 20 / 20 | 320 | 2 HU, 430 mm | 13 |
| BSA 0150-50 | 9 kHz ... 500 MHz | 50 / 70 | 47 / 49 ±2 | 20 / 20 | 400 | 3 HU, 630 mm | 20 |
| BSA 0150-75 | 9 kHz ... 500 MHz | 75 / 90 | 48.8 / 51 ±2 | 20 / 20 | 700 | 3 HU, 630 mm | 21 |
| BSA 0150-100 | 9 kHz ... 500 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | 700 | 3 HU, 630 mm | 21 |
| BSA 0150-150 | 9 kHz ... 500 MHz | 150 / 180 | 51.8 / 54 ±2 | 20 / 20 | 820 | 3 HU, 630 mm | 21 |
| BSA 0150-500/300/100 | 9 kHz ... 500 MHz | | | | 2500 | 4 HU, 630 mm | 38 |
| | 9 kHz ... 250 MHz | 500 / 600 | 57 / 59 ±2 | 20 / 17 | | | |
| | 200 ... 400 MHz | 300 / 350 | 54.8 / 57 ±2 | 20 / 20 | | | |
| | 400 ... 500 kHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | | | |
| BSA 0150-500D | 9 kHz ... 500 MHz | | | | 2800 | 9 HU, 630 mm | 85 |
| | 9 kHz ... 250 MHz | 500 / 600 | 57 / 59 ±2 | 20 / 20 | | | |
| | 200 ... 500 MHz | 500 / 600 | 57 / 59 ±2 | 20 / 20 | | | |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm