

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0150-5	9 kHz ... 500 MHz	5 / 8	37 / 39 ±2	20 / 20	100	2 HU, 430 mm	11
BSA 0150-10	9 kHz ... 500 MHz	10 / 12	40 / 42 ±2	20 / 20	150	2 HU, 430 mm	12
BSA 0150-30	9 kHz ... 500 MHz	30 / 35	44.8 / 47 ±2	20 / 20	320	2 HU, 430 mm	13
BSA 0150-50	9 kHz ... 500 MHz	50 / 70	47 / 49 ±2	20 / 20	400	3 HU, 630 mm	20
BSA 0150-75	9 kHz ... 500 MHz	75 / 90	48.8 / 51 ±2	20 / 20	700	3 HU, 630 mm	21
BSA 0150-100	9 kHz ... 500 MHz	100 / 120	50 / 52 ±2	20 / 20	750	3 HU, 630 mm	21
BSA 0150-150	9 kHz ... 500 MHz	150 / 180	51.8 / 54 ±2	20 / 20	800	3 HU, 630 mm	21
BSA 0150-500/300/100	9 kHz ... 500 MHz				2500	4 HU, 630 mm	38
	9 kHz ... 250 MHz	500 / 600	57 / 59 ±2	20 / 17			
	200 ... 400 MHz	300 / 350	54.8 / 57 ±2	20 / 20			
	400 ... 500 kHz	100 / 120	50 / 52 ±2	20 / 20			
BSA 0150-500D	9 kHz ... 500 MHz				2800	9 HU, 630 mm	85
	9 kHz ... 250 MHz	500 / 600	57 / 59 ±2	20 / 20			
	200 ... 500 MHz	500 / 600	57 / 59 ±2	20 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm