

**STANDARD MODELS**

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 1010-10	100 kHz ... 100 MHz	10 / 15	40 / 42 ±2	20 / 20	150	2 HU, 430 mm	10
BSA 1010-30	100 kHz ... 100 MHz	30 / 35	44.8 / 47 ±2	20 / 20	350	2 HU, 430 mm	13
BSA 1010-50	100 kHz ... 100 MHz	50 / 70	47 / 49 ±2	20 / 20	280	2 HU, 430 mm	12
BSA 1010-125	100 kHz ... 100 MHz	125 / 140	51 / 53 ±2	20 / 20	510	2 HU, 430 mm	14
BSA 1010-150	100 kHz ... 100 MHz	150 / 200	51.8 / 54 ±2	20 / 20	550	3 HU, 630 mm	14
BSA 1010-250	100 kHz ... 100 MHz	250 / 280	54 / 56 ±2	20 / 20	900	3 HU, 630 mm	29
BSA 1010-400	100 kHz ... 100 MHz	400 / 450	56 / 58 ±2	20 / 20	1900	4 HU, 630 mm	39
BSA 1010-500	100 kHz ... 100 MHz	500 / 600	57 / 59 ±2	20 / 18	2800	5 HU, 630 mm	45
BSA 1010-600	100 kHz ... 100 MHz	600 / 750	57.8 / 60 ±2	20 / 20	3000	5 HU, 630 mm	45
BSA 1010-1000	100 kHz ... 100 MHz	1000 / 1700	60 / 62 ±2	20 / 20	3100	5 HU, 630 mm	65
BSA 1010-1200	100 kHz ... 100 MHz	1200 / 1300	60.8 / 63 ±2	20 / 20	6000	18 HU, 800 mm	175
BSA 1010-1500	100 kHz ... 100 MHz	1500 / 1700	61.8 / 64 ±2	20 / 20	10000	24 HU, 800 mm	290

For individual data sheets, please click on the above model name

1 HU = 44.45 mm