

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 1025-40	100 kHz ... 250 MHz	40 / 45	46 / 48 ±2	20 / 20	350	2 HU, 430 mm	13
BSA 1025-100	100 kHz ... 250 MHz	100 / 110	50 / 52 ±2	20 / 20	510	2 HU, 430 mm	14
BSA 1025-150	100 kHz ... 250 MHz	150 / 170	51.8 / 54 ±2	20 / 20	650	2 HU, 430 mm	21
BSA 1025-200	100 kHz ... 250 MHz	200 / 240	53 / 55 ±2	20 / 20	800	3 HU, 630 mm	21
BSA 1025-250	100 kHz ... 250 MHz	250 / 280	54 / 56 ±2	20 / 20	800	3 HU, 630 mm	21
BSA 1025-400	100 kHz ... 250 MHz	400 / 450	56 / 58 ±2	20 / 20	1900	4 HU, 630 mm	37
BSA 1025-500	100 kHz ... 250 MHz	500 / 600	57 / 59 ±2	20 / 18	2300	4 HU, 630 mm	52
BSA 1025-1000	100 kHz ... 250 MHz	1000 / 1100	60 / 62 ±2	20 / 20	3100	5 HU, 630 mm	65
BSA 1025-1250	100 kHz ... 250 MHz	1250 / 1350	61 / 63 ±2	20 / 20	6500	10 HU, 630 mm	110
BSA 1025-2500	100 kHz ... 250 MHz	2500 / 2700	64 / 66 ±2	20 / 20	13000	24 HU, 800 mm	265

For individual data sheets, please click on the above model name

1 HU = 44.45 mm