

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 1040-600/350	100 kHz ... 400 MHz				2800	5 HU, 630 mm	45
	100 kHz ... 100 MHz	600 / 700	57.8 / 60 ±2	20 / 20			
	100 ... 250 MHz	500 / 600	57 / 59 ±2	20 / 20			
	250 ... 400 MHz	350 / 400	55.4 / 57 ±2	20 / 20			

1 HU = 44.45 mm

STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	P_N -0.5 dB min. at VSWR 2:1
Spurious (at P_N):	-60 dBc min. (excluding harmonics)
Class of Operation:	A-linear

GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	N-f, standard on rear panel
Mains Supply:	200 ... 240 V AC ±10%, 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G
Cooling:	forced air with integral blower air intake from front, air exhaust at rear Option W: Liquid cooling External heat exchanger required

OPTIONS

A) RF Monitor Outputs	L) LAN Remote Control
B) External Dual Directional Coupler	R) RS-232C/RS-485 Remote Control

BSA 100 kHz ... 400 MHz Solid State Amplifiers

C) IEEE-488.2 GPIB Remote Control

D) Front Panel RF Connectors

E) RF Power Indication (digital)

F) Gain Adjustment

H) DC Supply

S) Internal RF Switching Unit

U) USB Remote Control

W) Liquid Cooling

X) External Control of other Amplifiers

(XL) Rack width 800 mm