

STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 4060-2	4 ... 6 GHz	2 / 2.5	33 / 35 ±2	20 / 20	75	2 HU, 430 mm	10
BLMA 4060-4	4 ... 6 GHz	4 / 4.5	36 / 38 ±2	20 / 20	80	2 HU, 430 mm	10
BLMA 4060-10	4 ... 6 GHz	10 / 11	40 / 42 ±2	20 / 20	150	2 HU, 430 mm	10
BLMA 4060-20	4 ... 6 GHz	20 / 22	43 / 45 ±2	20 / 20	300	2 HU, 430 mm	13
BLMA 4060-40	4 ... 6 GHz	40 / 45	46 / 48 ±2	20 / 20	350	2 HU, 430 mm	13
BLMA 4060-50	4 ... 6 GHz	50 / 60	47 / 49 ±2	20 / 20	500	2 HU, 430 mm	14
BLMA 4060-100	4 ... 6 GHz	100 / 120	50 / 53 ±3	20 / 20	1050	3 HU, 430 mm	21
BLMA 4060-200	4 ... 6 GHz	200 / 230	53 / 55 ±2	20 / 20	3000	4 HU, 630 mm	51
BLMA 4060-400	4 ... 6 GHz	400 / 450	56 / 58 ±2	20 / 20	6000	6 HU, 630 mm	56
BLMA 4060-850	4 ... 6 GHz	850 / 900	59.3 / 60 ±2	20 / 20	13000	15 HU, 800 mm	200

For individual data sheets, please click on the above model name

1 HU = 44.45 mm