

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 4018-5	4 ... 18 GHz	5 / 6	37 / 39 ±2	18 / 20	200	2 HU, 430 mm	12
BLMA 4018-10	4 ... 18 GHz	10 / 12	40 / 44 ±4	12 / 15	300	2 HU, 430 mm	13
BLMA 4018-20/15D	4 ... 18 GHz	20 / 25	43 / 45 ±2	20 / 20	380	3 HU, 430 mm	21
	4 ... 6 GHz	15 / 18	41.8 / 46 ±4	15 / 20			
BLMA 4018-20	4 ... 18 GHz	20 / 22	43 / 47 ±4	15 / 15	600	3 HU, 630 mm	23
BLMA 4018-20D	4 ... 18 GHz	20 / 25	43 / 45 ±2	20 / 20	400	3 HU, 430 mm	23
	4 ... 6 GHz	20 / 22	43 / 46 ±3	15 / 20			
	6 ... 18 GHz						
BLMA 4018-30D	4 ... 18 GHz	30 / 35	44.8 / 47 ±2	20 / 20	700	4 HU, 630 mm	37
	4 ... 6 GHz	30 / 35	44.8 / 47 ±3	15 / 20			
	6 ... 18 GHz						
BLMA 4018-40/35D	4 ... 18 GHz	40 / 45	46 / 48 ±2	20 / 20	700	4 HU, 630 mm	37
	4 ... 6 GHz	35 / 40	45.4 / 48 ±3	15 / 20			
	6 ... 18 GHz						

For individual data sheets, please click on the above model name

1 HU = 44.45 mm