

## STANDARD MODELS

| Model       | Frequency Range | Output Power<br>$P_N$ min / typ<br>W | Gain<br>min / typ<br>dB | Harmonics<br>2nd / 3rd<br>dBc | Line Power<br>VA | Dimensions<br>(H, D)<br>19"-System | Weight<br>kg |
|-------------|-----------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BLMA 6018-7 | 6 ... 18 GHz    | 7 / 8                                | 38.5 / 43 ±4            | 15 / 20                       | 200              | 2 HU, 430 mm                       | 11           |

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

|                       |   |
|-----------------------|---|
| Input Power:          | 0 dBm (1 mW) max.                               |
| Overdrive Protection: | up to +10 dBm for no damage                     |
| Input Impedance:      | 50 Ohm nominal                                  |
| Output Impedance:     | 50 Ohm nominal                                  |
| Input VSWR:           | <2:1 typ.                                       |
| Load VSWR:            | infinite for no damage (100% mismatch tolerant) |
|                       | $P_N$ -0.5 dB min. at VSWR 2:1                  |
| Spurious (at $P_N$ ): | -60 dBc min. (excluding harmonics)              |
| Class of Operation:   | A-linear or AB-linear                           |

## GENERAL

|                      |   |
|----------------------|---|
| RF Input:            | SMA-f, standard on front panel  |
| RF Output:           | SMA-f, standard on front panel  |
| Mains Supply:        | 100 ... 240 V AC, 47 ... 63 Hz  |
| Elapsed Time Meter:  | via status display  |
| Ambient Temperature: | 0 ... +45 °C  |
| Storage Temperature: | -25 ... 85 °C   |
| Relative Humidity:   | up to 95% (non-condensing)  |
| Operating Altitude:  | up to 2000 m above sea level  |
| Vibration and Shock: | MIL-STD-810 G   |
| Cooling:             | forced air with integral blower<br>air intake from front, air exhaust at rear |

## OPTIONS

|                                      |   |
|--------------------------------------|---|
| A) RF-Sample Ports *)                | L) LAN Remote Control                   |
| B) External Dual Directional Coupler | N) Harmonics Filtering *)               |
| C) IEEE-488.2 GPIB Remote Control    | R) RS-232C/RS-485 Remote Control        |
| D) Rear Panel RF Connectors          | S) Internal RF Switching Unit *)        |
| E) RF Power Indication (digital) *)  | U) USB Remote Control                   |
| F) Gain Adjustment *)                | W) Liquid Cooling                       |
| G) Output Isolator *)                | X) External Control of other Amplifiers |
| H) DC Supply                         |   |

**BLMA** 6 ... 18 GHz  
Solid State Amplifiers

I) 3x 208 V AC / 60 Hz

\*) These options may reduce output power and/or gain