

STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 2640-0.1	26.5 ... 40 GHz	0.1 / 0.12	20 / 23 ±3	20 / 20	50	2 HU, 430 mm	9
BLMA 2640-0.2	26.5 ... 40 GHz	0.2 / 0.23	23 / 26 ±3	20 / 20	50	2 HU, 430 mm	9
BLMA 2640-0.3	26.5 ... 40 GHz	0.3 / 0.35	25 / 28 ±3	20 / 20	90	2 HU, 430 mm	9
BLMA 2640-0.5	26.5 ... 40 GHz	0.5 / 0.6	27 / 30 ±3	20 / 20	90	2 HU, 430 mm	10
BLMA 2640-0.8	26.5 ... 40 GHz	0.8 / 1	29 / 32 ±3	20 / 20	90	2 HU, 430 mm	10
BLMA 2640-1	26.5 ... 40 GHz	1 / 1.1	30 / 34 ±4	20 / 20	110	2 HU, 430 mm	11
BLMA 2640-1.5	26.5 ... 40 GHz	1.5 / 1.6	31.8 / 36 ±4	20 / 20	120	2 HU, 430 mm	12
BLMA 2640-2	26.5 ... 40 GHz 26.5 ... 36 GHz 36 ... 40 GHz	2 / 2.1 1.6 / 1.8	33 / 37 ±4 32 / 36 ±4	20 / 20 20 / 20	150	2 HU, 430 mm	12
BLMA 2640-4D	26.5 ... 40 GHz 26.5 ... 31 GHz 31 ... 40 GHz	4 / 4.5 4 / 4.25	36 / 40 ±4 36 / 40 ±4	20 / 20 20 / 20	300	2 HU, 430 mm	13
BLMA 2640-5	26.5 ... 40 GHz	5 / 5.5	37 / 41 ±4	20 / 20	300	2 HU, 430 mm	13
BLMA 2640-8	26.5 ... 40 GHz	8 / 9	39 / 43 ±4	20 / 20	300	2 HU, 430 mm	14
BLMA 2640-10	26.5 ... 40 GHz	10 / 11	40 / 44 ±4	20 / 20	400	2 HU, 430 mm	14
BLMA 2640-15	26.5 ... 40 GHz	15 / 18	41.8 / 46 ±4	20 / 20	400	2 HU, 430 mm	14
BLMA 2640-20	26.5 ... 40 GHz	20 / 22	43 / 47 ±4	20 / 20	500	3 HU, 630 mm	21
BLMA 2640-40	26.5 ... 40 GHz	40 / 44	46 / 50 ±4	20 / 20	900	4 HU, 630 mm	27
BLMA 2640-60	26.5 ... 40 GHz	60 / 66	47.8 / 52 ±4	20 / 20	1000	6 HU, 630 mm	45
BLMA 2640-80	26.5 ... 40 GHz	80 / 88	49 / 53 ±4	20 / 20	1500	8 HU, 630 mm	65
BLMA 2640-100	26.5 ... 40 GHz	100 / 110	50 / 54 ±4	20 / 20	2000	8 HU, 630 mm	65
BLMA 2640-200	26.5 ... 40 GHz	200 / 220	53 / 57 ±4	20 / 20	6000	12 HU, 630 mm	80

For individual data sheets, please click on the above model name

1 HU = 44.45 mm