

## STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0125-125	9 kHz ... 250 MHz	125 / 150	51 / 53 ±2	20 / 20	530	2 HU, 430 mm	14

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	$P_N$ -0.5 dB min. at VSWR 2:1
Spurious (at $P_N$ ):	-60 dBc min. (excluding harmonics)
Class of Operation:	A-linear

## GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	N-f, standard on rear panel
Mains Supply:	100 ... 240 V AC ±10%, 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-25 ... 85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G
Cooling:	forced air with integral blower air intake from front, air exhaust at rear Option W: Liquid cooling External heat exchanger required

## OPTIONS

A) RF Monitor Outputs	L) LAN Remote Control
B) External Dual Directional Coupler	R) RS-232C/RS-485 Remote Control
C) IEEE-488.2 GPIB Remote Control	S) Internal RF Switching Unit
D) Front Panel RF Connectors	U) USB Remote Control
E) RF Power Indication (digital)	W) Liquid Cooling
F) Gain Adjustment	X) External Control of other Amplifiers

**BSA** 9 kHz ... 250 MHz  
Solid State Amplifiers

H) DC Supply

(XL) Rack width 800 mm