

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 0211-100	20 ... 110 MHz	100 / 120	50 / 52 ±2	20 / 15	450	3 HU, 630 mm	20
BLWA 0211-200	20 ... 110 MHz	200 / 250	53 / 55 ±2	20 / 15	800	3 HU, 630 mm	30
BLWA 0211-500	20 ... 110 MHz	500 / 600	57 / 59 ±2	20 / 15	1800	4 HU, 630 mm	35
BLWA 0211-1000	20 ... 110 MHz	1000 / 1100	60 / 62 ±2	20 / 12	3000	5 HU, 630 mm	46
BLWA 0211-1250	20 ... 110 MHz	1250 / 1400	61 / 63 ±2	20 / 15	5000	9 HU, 630 mm	100
BLWA 0211-1800	20 ... 110 MHz	1800 / 2000	62.5 / 65 ±2	20 / 15	7500	11 HU, 630 mm	135
BLWA 0211-2500	20 ... 110 MHz	2500 / 2700	64 / 66 ±2	20 / 15	9800	12 HU, 800 mm	175
BLWA 0211-3000	20 ... 110 MHz	3000 / 3300	64.8 / 67 ±2	20 / 15	20000	18 HU, 800 mm	300
BLWA 0211-4000	20 ... 110 MHz	4000 / 4500	66 / 68 ±2	20 / 15	23000	24 HU, 800 mm	400
BLWA 0211-5000	20 ... 110 MHz	5000 / 5500	67 / 69 ±2	20 / 15	30000	37 HU, 800 mm	460
BLWA 0211-7000	20 ... 110 MHz	7000 / 8000	68.4 / 71 ±2	20 / 15	35000	2x 37 HU, 800 mm	590
BLWA 0211-10000	20 ... 110 MHz	10000 / 11000	70 / 72 ±2	20 / 12	60000	2x 37 HU, 800 mm	1000

For individual data sheets, please click on the above model name

1 HU = 44.45 mm