

STANDARD MODELS

Model	Frequency Range	Output Power P _p min / Duty W _{pk} / %	Pulse Width max. **)	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BPA 0305-50	300 ... 500 MHz	50 / 10	100 µs	47 / 48.5 ±1.5	20 / 20	80	2 HU, 430 mm	25
BPA 0305-100	300 ... 500 MHz	100 / 10	100 µs	50 / 51.5 ±1.5	20 / 20	150	2 HU, 430 mm	25
BPA 0305-250	300 ... 500 MHz	250 / 10	100 µs	54 / 55.5 ±1.5	20 / 20	250	4 HU, 630 mm	30
BPA 0305-500	300 ... 500 MHz	500 / 10	100 µs	57 / 58.5 ±1.5	20 / 20	350	4 HU, 630 mm	40
BPA 0305-1000	300 ... 500 MHz	1000 / 10	100 µs	60 / 61.5 ±1.5	20 / 20	500	4 HU, 630 mm	45
BPA 0305-2000	300 ... 500 MHz	2000 / 10	100 µs	63 / 64.5 ±1.5	20 / 20	750	6 HU, 630 mm	55
BPA 0305-4000	300 ... 500 MHz	4000 / 10	100 µs	66 / 67.5 ±1.5	20 / 20	1000	7 HU, 630 mm	75
BPA 0305-7000	300 ... 500 MHz	7000 / 10	100 µs	68 / 69.5 ±1.5	20 / 20	2000	12 HU, 800 mm	115

For individual data sheets, please click on the above model name

1 HU = 44.45 mm