

STANDARD MODELS

Model	Frequency Range	Output Power P _p min / Duty W _{pk} / %	Pulse Width max. **)	Gain typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BPA 0410-250	400 ... 1000 MHz	250 / 10	100 µs	54 ±2	15 / 20	500	3 HU, 430 mm	22
BPA 0410-1000	400 ... 1000 MHz	1000 / 10	100 µs	60 ±2	15 / 20	900	4 HU, 630 mm	32
BPA 0410-1200	400 ... 1000 MHz	1200 / 10	100 µs	61 ±2	15 / 20	1000	5 HU, 630 mm	55
BPA 0410-2000	400 ... 1000 MHz	2000 / 10	100 µs	63 ±2	15 / 20	2000	9 HU, 630 mm	90
BPA 0410-4000	400 ... 1000 MHz	4000 / 10	100 µs	66 ±2	20 / 20	4000	12 HU, 630 mm	155
BPA 0410-5000P6	400 ... 1000 MHz	5000 / 6	100 µs	67 ±2	15 / 20	4500	24 HU, 800 mm	140
BPA 0410-10000P4	400 ... 1000 MHz	10000 / 4	40 µs	70 ±2	15 / 20	4500	24 HU, 800 mm	250
BPA 0410-10000P6	400 ... 1000 MHz	10000 / 6	100 µs	70 ±2	15 / 20	9000	24 HU, 800 mm	260
BPA 0410-13000P6	400 ... 1000 MHz	13000 / 6	100 µs	71.1 ±2	15 / 20	12000	37 HU, 800 mm	320
BPA 0410-20000P6	400 ... 1000 MHz	20000 / 6	100 µs	73 ±2	15 / 20	15000	37 HU, 800 mm	350

For individual data sheets, please click on the above model name

1 HU = 44.45 mm