

STANDARD MODELS

Model	Frequency Range	Output Power P _p min / Duty W _{pk} / %	Pulse Width max. **)	Gain typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BPA 0913-100	950 ... 1250 MHz	100 / 5	100 µs	50 ±2.5	40 / 40	300	2 HU, 430 mm	15
BPA 0913-500	950 ... 1250 MHz	500 / 5	100 µs	57 ±2.5	40 / 40	300	3 HU, 630 mm	25
BPA 0913-1000	950 ... 1250 MHz	1000 / 5	2 µs	60 ±2.5	30 / 30	1400	3 HU, 630 mm	21
BPA 0913-2500	950 ... 1250 MHz	2500 / 10	100 µs	64 ±2	30 / 30	2100	4 HU, 630 mm	34
BPA 0913-4000	950 ... 1250 MHz	4000 / 5	100 µs	66 ±2.5	40 / 40	1200	12 HU, 800 mm	120
BPA 0913-7500	950 ... 1250 MHz	7500 / 5	100 µs	68 ±2.5	40 / 40	2500	24 HU, 800 mm	220

For individual data sheets, please click on the above model name 1 HU = 44.45 mm