

STANDARD MODELS

| Model         | Frequency Range  | Output Power<br>P <sub>p</sub> min / Duty<br>W <sub>pk</sub> / % | Pulse Width<br>max. **) | Gain<br>typ<br>dB | Harmonics<br>2nd / 3rd<br>dBc | Line Power<br>VA | Dimensions<br>(H, D)<br>19"-System | Weight<br>kg |
|---------------|------------------|--|-------------------------|-------------------|-------------------------------|------------------|------------------------------------|--------------|
| BPA 0913-100  | 950 ... 1250 MHz | 100 / 5  | 100 µs                  | 50 ±2.5           | 40 / 40                       | 300              | 2 HU, 430 mm                       | 15           |
| BPA 0913-500  | 950 ... 1250 MHz | 500 / 5  | 100 µs                  | 57 ±2.5           | 40 / 40                       | 300              | 3 HU, 630 mm                       | 25           |
| BPA 0913-1000 | 950 ... 1250 MHz | 1000 / 5   | 2 µs                    | 60 ±2.5           | 30 / 30                       | 1400             | 3 HU, 630 mm                       | 21           |
| BPA 0913-2500 | 950 ... 1250 MHz | 2500 / 10  | 100 µs                  | 64 ±2             | 30 / 30                       | 2100             | 4 HU, 630 mm                       | 34           |
| BPA 0913-4000 | 950 ... 1250 MHz | 4000 / 5   | 100 µs                  | 66 ±2.5           | 40 / 40                       | 1200             | 12 HU, 800 mm                      | 120          |
| BPA 0913-7500 | 950 ... 1250 MHz | 7500 / 5   | 100 µs                  | 68 ±2.5           | 40 / 40                       | 2500             | 24 HU, 800 mm                      | 220          |

For individual data sheets, please click on the above model name 1 HU = 44.45 mm