

**STANDARD MODELS**

| Model         | Frequency Range   | Output Power<br>P <sub>p</sub> min / Duty<br>W <sub>pk</sub> / % | Pulse Width<br>max. **) | Gain<br>min / typ<br>dB | Harmonics<br>2nd / 3rd<br>dBc | Line Power<br>VA | Dimensions<br>(H, D)<br>19"-System | Weight<br>kg |
|---------------|-------------------|--|-------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BPA 1114-900  | 1150 ... 1450 MHz | 900 / 10   | 100 µs                  | 60 / 62.5 ±2.5          | 30 / 30                       | 600              | 3 HU, 630 mm                       | 22           |
| BPA 1114-1500 | 1150 ... 1450 MHz | 1500 / 10  | 100 µs                  | 62.4 / 65 ±2.5          | 30 / 30                       | 1400             | 3 HU, 630 mm                       | 30           |
| BPA 1114-2250 | 1150 ... 1450 MHz | 2250 / 10  | 100 µs                  | 63.5 / 66 ±2.5          | 30 / 30                       | 2000             | 4 HU, 630 mm                       | 42           |
| BPA 1114-2700 | 1150 ... 1450 MHz | 2700 / 10  | 100 µs                  | 64.3 / 67 ±2.5          | 30 / 30                       | 2500             | 6 HU, 630 mm                       | 65           |
| BPA 1114-4500 | 1150 ... 1450 MHz | 4500 / 10  | 100 µs                  | 66.5 / 69 ±2.5          | 30 / 30                       | 5000             | 8 HU, 630 mm                       | 80           |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm