

## STANDARD MODELS

Model	Frequency Range	Output Power P <sub>P</sub> min / Duty W pk / %	Pulse Width max. **)	Gain typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BPA 1214-1750	1.2 ... 1.4 GHz	1750 / 10	100 µs	62.4 ±2	30 / 30	1200	4 HU, 630 mm	35

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	P <sub>N</sub> -0.5 dB min. at VSWR 2:1
PRF at 1 µs Pulswidth	100 kHz (Duty 6 ... 10%)
PRF at 100 µs Pulswidth	1 kHz (Duty 6 ... 10%)
Pulse Droop:	1.0 dB max.
Spurious (at P <sub>N</sub> ):	-60 dBc min. (excluding harmonics)
Class of Operation:	C

## GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	7-16-f, standard on rear panel
Mains Supply:	200 ... 240 V AC ±10%, 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G
Cooling:	forced air with integral blower air intake from front, air exhaust at rear

## OPTIONS

A) Sample Ports *)	R) RS-232C/RS-485 Remote Control
B) External Dual Directional Coupler	S) Internal RF Switching Unit *)
C) IEEE-488.2 GPIB Remote Control	U) USB Remote Control
D) Front Panel RF-Connectors	W) Liquid Cooling
E) RF Power Indication (digital) *)	X) External Control of other Amplifiers

# BPA 1.2 ... 1.4 GHz Pulsed Solid State Amplifiers

F) Gain Adjustment \*)  
G) Output Isolator \*)  
H) DC-Supply  
I) 3x 208 V AC / 60 Hz  
L) LAN Remote Control

\*) These options may reduce output power and/or gain  
\*\*) Optionally other pulse width available