

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0106-25/10D	9 kHz ... 6000 MHz				240	3 HU, 430 mm	18
	9 kHz ... 250 MHz	25 / 30	44 / 46 ±2	20 / 20			
	200 ... 1000 MHz	25 / 30	44 / 46 ±2	20 / 20			
	1000 ... 6000 MHz	10 / 15	40 / 43 ±3	20 / 20			
BSA 0106-25D	9 kHz ... 6000 MHz				420	3 HU, 430 mm	19
	9 kHz ... 500 MHz	25 / 30	44 / 46 ±2	20 / 20			
	500 ... 6000 MHz	25 / 30	44 / 47 ±3	20 / 20			
BSA 0106-75D	9 kHz ... 6000 MHz				1000	3 HU, 630 mm	32
	9 kHz ... 400 MHz	75 / 85	48.8 / 51 ±2	20 / 20			
	400 ... 1000 MHz	75 / 85	48.8 / 51 ±2	20 / 20			
	1000 ... 6000 MHz	75 / 85	48.8 / 52 ±3	18 / 20			
BSA 0106-100D	9 kHz ... 6000 MHz				1500	4 HU, 630 mm	45
	9 kHz ... 400 MHz	100 / 110	50 / 52 ±2	20 / 20			
	400 ... 1000 MHz	100 / 110	50 / 52 ±2	20 / 20			
	1000 ... 6000 MHz	100 / 110	50 / 53 ±3	18 / 20			
BSA 0106-200D	9 kHz ... 6000 MHz				3200	8 HU, 630 mm	82
	9 kHz ... 400 MHz	200 / 220	53 / 55 ±2	20 / 20			
	400 ... 1000 MHz	200 / 220	53 / 55 ±2	20 / 20			
	1000 ... 6000 MHz	200 / 220	53 / 56 ±3	20 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm