

STANDARD MODELS

| Model | Frequency Range | Output Power P_N min / typ W | Gain min / typ dB | Harmonics 2nd / 3rd dBc | Line Power VA | Dimensions (H, D) 19"-System | Weight kg |
|--------------------|--------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BSA 0103-25/20D | 9 kHz ... 3000 MHz | | | | 400 | 3 HU, 430 mm | 19 |
| | 9 kHz ... 500 MHz | 25 / 30 | 44 / 46 ±2 | 20 / 20 | | | |
| | 500 ... 3000 MHz | 20 / 25 | 43 / 46 ±3 | 15 / 20 | | | |
| BSA 0103-40/30/20D | 9 kHz ... 3000 MHz | | | | 400 | 3 HU, 630 mm | 25 |
| | 9 kHz ... 250 MHz | 40 / 50 | 46 / 48 ±2 | 20 / 20 | | | |
| | 200 ... 1000 MHz | 30 / 40 | 44.8 / 47 ±2 | 20 / 20 | | | |
| | 1000 ... 3000 MHz | 20 / 25 | 43 / 46 ±3 | 15 / 20 | | | |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm