

STANDARD MODELS

Model	Frequency Range	Output Power P _p min / Duty W _{pk} / %	Pulse Width max. **)	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BPA 1020-250	1 ... 2 GHz	250 / 10	100 µs	54 / 57 ±3	15 / 20	500	3 HU, 430 mm	22
BPA 1020-1000	1 ... 2 GHz	1000 / 10	100 µs	60 / 63 ±3	20 / 20	2200	4 HU, 630 mm	48
BPA 1020-2000	1 ... 2 GHz	2000 / 10	100 µs	63 / 66 ±3	15 / 20	4000	7 HU, 630 mm	75
BPA 1020-4000	1 ... 2 GHz	4000 / 10	100 µs	66 / 69 ±3	15 / 20	5000	12 HU, 800 mm	160
BPA 1020-6000	1 ... 2 GHz	6000 / 10	100 µs	67.8 / 71 ±3	15 / 20	7500	16 HU, 800 mm	240
BPA 1020-8000	1 ... 2 GHz	8000 / 10	100 µs	69 / 72 ±3	15 / 20	12000	24 HU, 800 mm	330
BPA 1020-11000	1 ... 2 GHz	11000 / 10	100 µs	70.4 / 74 ±3	15 / 20	15000	37 HU, 800 mm	440
BPA 1020-15000	1 ... 2 GHz	15000 / 10	100 µs	71.8 / 75 ±3	15 / 20	20000	41 HU, 800 mm	600
BPA 1020-20000	1 ... 2 GHz	20000 / 10	100 µs	73 / 76 ±3	15 / 20	30000	2x 37 HU, 800 mm	800
BPA 1020-20000W	1 ... 2 GHz	20000 / 10	100 µs	73 / 76 ±3	15 / 20	30000	2x 32 HU, 800 mm	730

For individual data sheets, please click on the above model name

1 HU = 44.45 mm