

## STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 0240-5/3/0.8	20 MHz ... 40 GHz				200	3 HU, 430 mm	18
	20 MHz ... 1000 kHz	5 / 6	37 / 39 ±2	20 / 20			
	1 ... 18 GHz	3 / 3.3	34.8 / 39 ±4	15 / 15			
	18 ... 40 GHz	0.8 / 0.9	29 / 33 ±4	7 / 15			

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	$P_N$ -0.5 dB min. at VSWR 2:1
Spurious (at $P_N$ ):	-60 dBc min. (excluding harmonics)
Class of Operation:	A-linear

## GENERAL

RF Input:	2.92 mm-f, standard on front panel
RF Output:	2.92 mm-f, standard on front panel
Mains Supply:	100 ... 240 V AC, 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-25 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G
Cooling:	forced air with integral blower air intake from front, air exhaust at rear Option W: Liquid cooling External heat exchanger required

## OPTIONS

A) RF-Sample Ports	L) LAN Remote Control
B) External Dual Directional Coupler	P) Precise RMS RF Power Sensor (internal)

# BLWA 20 MHz ... 40 GHz Solid State Amplifiers

- C) IEEE-488.2 GPIB Remote Control
- D) Front Panel RF Connectors
- E) RF Power Indication (digital)
- F) Gain Adjustment
- H) DC Supply
- I) 3x 208 V AC / 60 Hz
- R) RS-232C/RS-485 Remote Control
- S) Internal RF Switching Unit
- U) USB Remote Control
- W) Liquid Cooling
- X) External Control of other Amplifiers