

BDC 0.7 ... 8 GHz Directional Coupler

STANDARD MODELS

Model	Frequency Range X)	Coupling X) dB	Power P _{min} W	Insertion Loss max dB	Directivity min dB	VSWR max Main Line	Main Line Connector	Coupling Line Connector
BDC 0780-20/200	0.7 ... 8 GHz	20 ±2	0 / 0 ±0	0 / 0	0	2 HU, 430 mm	0	SMA-f
BDC 0780-30/500	0.7 ... 8 GHz	30 ±2	0 / 0 ±0	0 / 0	0	2 HU, 430 mm	0	SMA-f
BDC 0780-40/500	0.7 ... 8 GHz	40 ±2	0 / 0 ±0	0 / 0	0	2 HU, 430 mm	0	SMA-f
BDC 0780-50/500	0.7 ... 8 GHz	50 ±2	0 / 0 ±0	0 / 0	0	2 HU, 430 mm	0	SMA-f

For individual data sheets, please click on the above model name
S: Single directional coupler

Notice:

Under normal operating conditions all Directional Couplers do not need to be mounted to a heatsink. However, if the units permanently run into high mismatch conditions at full rated power, the circuits will heat up significantly. In this case, we would recommend the units be mounted to a suitable heatsink or metal surface, capable to maintain a baseplate temperature of +60°C max.