

## STANDARD MODELS

Model	Frequency Range	Output Power $P_N$ min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 1006-150/30/10D	100 kHz ... 6 GHz				800	3 HU, 630 mm	29
	100 kHz ... 500 MHz	150 / 180	51.8 / 54 ±2	20 / 18			
	500 ... 2500 MHz	30 / 35	44.8 / 48 ±3	18 / 20			
	2500 ... 6000 MHz	10 / 15	40 / 43 ±3	20 / 20			

1 HU = 44.45 mm

## STANDARD SPECIFICATIONS

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	infinite for no damage (100% mismatch tolerant)
	$P_N$ -0.5 dB min. at VSWR 2:1
Spurious (at $P_N$ ):	-60 dBc min. (excluding harmonics)
Class of Operation:	A-linear

## GENERAL

RF Input:	N-f, standard on rear panel
RF Output:	N-f, standard on rear panel
Mains Supply:	200 ... 240 V AC, 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-25 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 G
Cooling:	forced air with integral blower air intake from front, air exhaust at rear Option W: Liquid cooling External heat exchanger required

## OPTIONS

A) RF Monitor Outputs	L) LAN Remote Control
B) External Dual Directional Coupler	R) RS-232C/RS-485 Remote Control

# BSA 100 kHz ... 6 GHz Solid State Amplifiers

C) IEEE-488.2 GPIB Remote Control  
D) Front Panel RF Connectors  
E) RF Power Indication (digital)  
F) Gain Adjustment  
H) DC Supply

S) Internal RF Switching Unit  
U) USB Remote Control  
W) Liquid Cooling  
X) External Control of other Amplifiers  
(XL) Rack width 800 mm